

Compact and Enhanced Presence Detection

You know it makes PIRfect Sense

Timeguard take PIR Presence Detectors to the next level for optimum coverage and control.



LEDs
UP TO
250W

SLW360N

- Slimline sensor head design.
- 360° area of detection with up to an 8m detection range for motion and 4m for presence detection at a 3m mounting height.
- IP44 weatherproof rating (internal use only).
- Manual override.
- Adjustable time setting: 3 seconds – 18 minutes.
- Adjustable 1 – 1000 LUX setting.
- Total PIR switching – 2000W halogen, 500W fluorescent, 250W LED lighting, 75W fan.



LEDs
UP TO
250W

SLFM360N

Features the same as the SLW360N, Plus:

- Flush mounting.
- 360° area of detection with up to an 8m detection range for motion and 4m for presence detection at a 3m mounting height.
- 75mm diameter ceiling cut-out.
- IP44 weatherproof rating (internal use only).



Quick and simple adjustment of 'Time ON' and 'Light Level (LUX)' settings.




Large, accessible wiring terminal block. Fixing pack and instructions enclosed.




360° area of detection, with up to an 8m diameter detection range (3m mounting height).

TOP VIEW



SIDE VIEW



Specification

	SLW360N	SLFM360N
Operating Voltage	230V AC	230V AC
1 or 2 Channel	1 Channel	1 Channel
Controls LED Lighting (max.)	250W	250W
1st Channel Filament/Halogen Loading (W)	2000	2000
1st Channel Fluorescent/ow Energy Loading (W)	500/150 CFL/Low Energy	500/150 CFL/Low Energy
Weatherproof Rating	IP44	IP44
Detection (metres max.)	8m	8m
Angle of Detection	360°	360°
Light ON Time after last (seconds min.)	3	3
Detection (Adjustable) – (minutes max.)	18	18
Permanent ON Facility	Electronic	Electronic
Adjustable light level control	•	•
EC Directives (conforms to latest directives)	•	•
Dimensions (mm – Height x Width x Depth)	53x103x103	71x84x84