

**What's NEW**

# Safe & Sound

## Emergency Assist Alarm Kit – Single Zone

The new all in one single zone control panel kit from Timeguard for areas where an emergency call for assistance may be required. Ideal for the home, shop conversions and small business installations.

EARB1N  
Reset Button



EAPC1N  
Pull Cord



EACP1N  
Single Zone Control Panel



Disabled Sticker



EADF1N  
Over Door Light

### EASZKN

#### Emergency Assist Alarm Kit – Single Zone

- Suitable for use where assistance may be required in WC areas, changing rooms, bedrooms etc.
- Each kit includes:  
1x Single Zone Control Panel – 2 gang.  
1x Reset Button – Single gang.  
1x Over Door Light – Single gang.  
1x Pull Cord.  
1x Disabled Sticker.
- Simple 2 wire connection from control panel to kit components.
- Slimline design.
- Control panel features audible and visual alerts.
- Illuminated over door light with audio output.
- Pull cord comes with ceiling mounted housing and 2m cord.

Complies with: EN60335-1: Household and similar electrical installations – safety. BS8300: The Design of buildings and their appliances to meet the needs of disabled people – Code of practice.

**SIMPLE**  
**2-WIRE CONNECTION**  
From Control Panel to Kit Components

# DALI Detectors

A range of DALI standard network detectors consisting of surface and flush mount options, power supply unit and remote control.

Detectors have varying detection patterns, 360° 9m or 360° 40m length x 5m width range, adjustable LUX settings and light ON times. DALI remote control has a 5m setting range.

PDSMDALI



### PDSMDALI

#### IR DALI Network System Detector – Surface Mount

- 360° 9m diameter detection.
- Adjustable time setting 10 seconds – 30 minutes.
- Adjustable standby time – ON/OFF, 1 – 30 minutes.
- Adjustable 10 – 1000 LUX setting.
- 15 selectable DALI groups.
- 1 light channel DALI broadcast.
- Remote control available – **Part No. IRRDALI.**

### PDSMCDALI

#### IR DALI Network System Corridor Detector – Surface Mount

- 360° 40m length x 5m width range of detection.
- 15 selectable DALI groups.
- 1 light channel DALI broadcast.
- Remote control available – **Part No. IRRDALI**

PDFMCDALI



### PDFMCDALI

#### IR DALI Network System Detector – Flush Mount

- 360° 9m diameter detection.
- Adjustable time setting 10 seconds – 30 minutes.
- Adjustable standby time – ON/OFF, 1 – 30 minutes.
- Adjustable 10 – 1000 LUX setting.
- 68mm diameter ceiling cut-out.
- 15 selectable DALI groups.
- 1 light channel DALI broadcast.
- Remote control available – **Part No. IRRDALI.**

### PDFMCDALI

#### IR DALI Network System Corridor Detector – Flush Mount

- 360° 40m length x 5m width range of detection.
- 15 selectable DALI groups.
- 1 light channel DALI broadcast.
- Remote control available – **Part No. IRRDALI**

PSUDALI



### PSUDALI

#### DALI Power Supply

- 230V 50Hz
- Rated power: 3.8W Max
- Output voltage: 16V DC
- Output current: 220mA
- Class rating: Class II
- IP20.
- For use with Timeguard DALI Sensor models:  
PDSMDALI, PDSMCDALI, PDFMCDALI and PDFMCDALI

IRRDALI



### IRRDALI

#### Infra-Red DALI Remote Control

- For use with Timeguard DALI Sensor models: PDSMDALI, PDSMCDALI, PDFMCDALI and PDFMCDALI.
- Ceiling mount presence detectors can be set up and adjusted without the use of ladders.
- Adjustable light (LUX) and time ON levels at the touch of a button.
- Easy to set by symbol recognition.
- IP40 Weatherproof rating.
- 5m (approx.) transmission range.
- 3V DC (CR2032 battery) factory fitted and replaceable.



for full details on these products please visit [www.timeguard.com](http://www.timeguard.com)